



(Business Registration No: 199400661M)

C-T430 Aircraft Tow Tractor

Operating Performance

Drawbar Pull	330kN
Drive Speed	28km/hr
Turning Radius	10010mm, 2 wheels steering, outside 6235mm, 4 wheels steering, outside

Weight and Dimensions

Gross Vehicle Weight	43t
Overall Dimension	6900mm(L)×2700mm(W)×2000mm(H)
Wheelbase	3200mm
Ground Clearance	200mm

Standard Equipment

Engine	Deutz TCD2013/L6, 200kw/2300rpm, 1110Nm/1500rpm
Transmission	ZF 6WG200 Power shift with torque converter, 6 speed forward/3 speed reverse
Axles	Kessler LT81, 4-wheels drive
Suspension	Front axle leaf spring, rear axle rigid mounted
Tires	14.00-24-28PR
Steering	Hydraulic power steering, 4 wheels steering
Steering mode	Front steering, rear steering, coordinated four wheels steering, and crab steering
Brakes	Dual circuit hydraulic dry disc brake, all wheels
Parking Brake	Spring loaded with hydraulic release
Electrical	24Volt DC, negative ground

Cab	Adjustable air vents, tinted windows opening side, intermittent two-speed windshield wiper and washer
Lights	Cab interior, headlight, stop/tail lights, turning signals, front and rear working lights, flashing beacon
Mirrors	Left and right main, right auxiliary, rear coupler
Options	<ul style="list-style-type: none"> Rear driver's station Elevating cab Air-con in cab Integrated hydraulic jack Autolub system Rear view camera

