

AIRPORT EQUIPMENT SERVICES PTE. LTD.

41 Kallang Pudding Road, #03-10 Golden Wheel Building, Singapore 349316 Phone: (65) 65421160 Fax: (65) 65421160 Email: aessg@singnet.com.sg Website: www.aessg.com

(Business Registration No: 199400661M)

THREE BOTTLE NITROGEN CART (MODEL NO: NC 299)



SPECIFICATION

Loading Capability : Three N2 Cylinder

Overall Length : 3130 mm Handle Extended

Overall Width : 1530 mm

Overall Height : 1170 mm Handle Up Weight : 250 kgs (Appr.)

Wheel : 400 - 8 Pneumatic Tyre Parking Brake : Mechanical Brake System

Max. Towing Speed : 25 km/h

Charging System :-

High Pressure : Inlet 6,000 psi & Outlet 25 - 4,000 psi Low Pressure : Inlet 5,000 psi & Outlet 0 - 250 psi Outlet Hose : 30 ft Length (not include adaptor)

SPECIFICATION OF NITROGEN CHARGING KIT

<u>Particulars</u>		<u>Qty</u>
Brand: TESCOM		
*	About unit is certified to be used for high pressure NITROGEN gas application, control cabinet with 2 outlet pressure range 0 - 4000 psi and 0-250 psi respectively one (1) each.	
1)	" Tescom " High Pressure Regulator (Inlet 4000 psi & Outlet 25 - 4000 psi)	1
2)	" Tescom " Low Pressure Regulator (Inlet 4000 psi & Outlet 0 - 250 psi)	1
3)	1/4" x 1 Meter Inlet Hose	3
4)	1/4" x 9 Meter Outlet Hose	2
5)	"Wika" 2" Dia. Inlet Gauge (0 - 4000 psi)	4
6)	"Wika" 2" Dia. Outlet Gauge (0-400 psi)	1
7)	1/4" Stainless Steel Needle Valve	3
8)	1/4" Air Safety Relief Valve	1
9)	Fitting (NPT)	1 set
10)	Brass Manifold	1
11)	Pressure Gauge Calibration Certificate (Certify by SIME-SIRIM Malaysia)	1 ea

^{*} This charging kit is not included charging adaptor