

AIRPORT EQUIPMENT SERVICES PTE. LTD.

41 Kallang Pudding Road, #03-10 Golden Wheel Building, Singapore 349316 Phone: (65) 65421160 Fax: (65) 65421160 Email: aessg@singnet.com.sg Website: www.aessg.com

(Business Registration No: 199400661M)

TK-WS40 Lavatory Service Vehicle



The TK-WS40 is design to collecting aircraft sewage and providing rinsing water to aircraft. It is in full compliance with CAAC and international standards, such as, IATA AHM 910, IATA AHM 913, IATA AHM 915, IATA AHM 970, MH/T 6014 etc.

Dimensions

Overall Dimensions6930*2100*2160 mmWheelbase3360 mmFront Wheel Tread1504 mmRear Wheel Tread1425 mmMinimum Turning Radius5600 mmGround Clearance330 mmGross Vehicle Weight5800 kg

Performance Data

| Maximum Speed | 40 km/hr |
|-----------------------------|------------------|
| Rinsing Water Tank Capacity | 1500 L |
| Sewage Tank Capacity | 2500 L |
| Platform Service Range | 400-3000 mm |
| Water Flow | \geq 150 L/min |
| Vacuity | 3.3 Kpa |

Applicable Aircraft:

A300, A310, A320, A340, BAe146, B727, B737, B747, B757, B767 etc

Standard Features

ISUZU Commercial Chassis ISUZU 4KH1-TCG40 Diese Engine Euro IV Emission Hydraulic Power Assisted Steering Leaf Spring Suspensions with Shock Absorber 5 Forward 1 Reverse Manual Transmission Centrifugal Pump Standard Lightings Adequte Warning Lights/Indicators Seperated Tank Design

Highlights

Safety Features

Drive Cabin AC

Emergency Stop Button Emergency Platform Descend Anti-collision Sensor Anti-skid Pavement **Winter Package** Heat-insulated Tank & Hose Heated Pump Chamber Heated Filter Chamer

Oval tank design, vaccum suction and hydraulic controled discharge valve, enabling a through discharge as well as a clearner efficient discharge operation.

Integrated 4mm thick 1Cr18Ni9 stainless steel water tank with wave-reducing panel, avoiding splashes and shocks during driving.

Diagram & Details









